

PRODUCT FOCUS

XL SUPER T8 SERIES, PREMIUM T8 & Watt Saver

Linear Fluorescent Lamp

- FOR >> INDUSTRIAL LIGHTING**
 >> **COMMERCIAL LIGHTING**
 >> **RESIDENTIAL LIGHTING**



MAX10494-10

F32T8/835XL
 F32T8/841XL
 F32T8/850XL
 F32T8/865XL

F32T8/25WS/835
 F32T8/25WS/841
 F32T8/25WS/850
 F32T8/28WS/835
 F32T8/28WS/841
 F32T8/28WS/850

F17T8/735
 F17T8/741
 F17T8/750
 F17T8/835
 F17T8/850
 F17T8/861

F25T8/735
 F25T8/741
 F25T8/835
 F25T8/841
 F25T8/850

F32T8/730
 F32T8/735
 F32T8/741
 F32T8/750
 F32T8/830

FB32T8/735
 FB32T8/741
 FB32T8/750

FB32T8/835
 FB32T8/841
 FB32T8/850



- **XL Super T8 & Premium Series**
 - >> High Lumen, Low Mercury
 - >> TCLP compliant (<5mg)
 - >> Finest blend of premium trichromatic rare earth phosphors
- **Watt Saver Series**
 - >> For Maximizing Energy Savings
 - >> Low Mercury - TCLP compliant (<5mg)

MaxLite™: 1-800-555-5629 Fax: 973-244-7300 info@maxlite.com www.maxlite.com

MaxLite West™: 1-800-793-1212 Fax: 909-944-1442 info@maxlite.com www.maxlite.com

PRODUCT FOCUS **XL SUPER T8 SERIES, PREMIUM T8 & Watt Saver**

Linear Fluorescent Lamp

F32T8/835XL 24,000 Hour (7) 6762751058 (8)*	F32T8/841XL 24,000 Hour (7) 6762751050 (2)*	F32T8/850XL 24,000 Hour (7) 6762751049 (6)*	F32T8/865XL 24,000 Hour (7) 6762751060 (1)*
F32T8/25WS/835 24,000 Hour (7) 6762751031 (1)*	F32T8/25WS/841 24,000 Hour (7) 6762751032 (8)*	F32T8/25WS/850 24,000 Hour (7) 6762751033 (5)*	
F32T8/28WS/835 24,000 Hour (7) 6762711209 (6)*	F32T8/28WS/841 24,000 Hour (7) 6762711208 (9)*	F32T8/28WS/850 24,000 Hour (7) 6762711210 (2)*	



XL SUPER T8 SERIES SPECIFICATIONS

Watts	Order Code	Description	Lumens	Lamp Life (Hrs)	CRI	Case Pack	Cathode Guard	K
32	51058	F32T8/835XL T8 4' High Lumen	3200	24,000▲	85	25	Y	3500
32	51050	F32T8/841XL T8 4' High Lumen	3200	24,000▲	85	25	Y	4100
32	51049	F32T8/850XL T8 4' High Lumen	3200	24,000▲	85	25	Y	5000
32	51060	F32T8/865XL T8 4' High Lumen	3200	24,000▲	85	25	Y	6500

Watt Saver T8 Series SPECIFICATIONS

Watts	Order Code	Description	Lumens	Lamp Life (Hrs)	CRI	Case Pack	Cathode Guard	K
25	51031	F32T8/25WS/835 Watt Saver 25W T8 4'	2400	24,000▲	85	25	Y	3500
25	51032	F32T8/25WS/841 Watt Saver 25W T8 4'	2400	24,000▲	85	25	Y	4100
25	51033	F32T8/25WS/850 Watt Saver 25W T8 4'	2400	24,000▲	85	25	Y	5000
28	11209	F32T8/28WS/835 Watt Saver 28W T8 4'	2725	24,000▲	85	25	Y	3500
28	11208	F32T8/28WS/841 Watt Saver 28W T8 4'	2725	24,000▲	85	25	Y	4100
28	11210	F32T8/28WS/850 Watt Saver 28W T8 4'	2725	24,000▲	85	25	Y	5000

MAX10494-10

All specifications are subject to change without notice

PRODUCT FOCUS **XL SUPER T8 SERIES,
PREMIUM T8 & Watt Saver**
Linear Fluorescent Lamp

F17T8/735 24,000 Hour (7) 6762751004 (5)*	F17T8/741 24,000 Hour (7) 6762751001 (4)*	F17T8/750 24,000 Hour (7) 6762751005 (2)*		
F17T8/835 24,000 Hour (7) 6762751006 (9)*	F17T8/841 24,000 Hour (7) 6762751002 (1)*	F17T8/850 24,000 Hour (7) 6762751007 (6)*		
F32T8/730 24,000 Hour (7) 6762751041 (0)*	F32T8/735 24,000 Hour (7) 6762751042 (7)*	F32T8/741 24,000 Hour (7) 6762751043 (4)*	F32T8/750 24,000 Hour (7) 6762751044 (1)*	
F25T8/735 24,000 Hour (7) 6762751024 (3)*	F25T8/741 24,000 Hour (7) 6762751021 (2)*	F25T8/835 24,000 Hour (7) 6762751026 (7)*	F25T8/841 24,000 Hour (7) 6762751022 (9)*	F25T8/850 24,000 Hour (7) 6762751027 (4)*



PREMIUM T8 SPECIFICATIONS

Watts	Order Code	Description	Initial Lumens	Mean Lumens	Lamp Life (Hrs)	CRI	Case Pack	Cathode Guard	K
17	51004	F17T8/735 T8 2'	1325	1260	24,000▲	75	25	Y	3500
17	51001	F17T8/741 T8 2'	1325	1260	24,000▲	75	25	Y	4100
17	51005	F17T8/750 T8 2'	1325	1260	24,000▲	75	25	Y	5000
17	51006	F17T8/835 T8 2'	1400	1330	24,000▲	85	25	Y	3500
17	51002	F17T8/841 T8 2'	1400	1330	24,000▲	85	25	Y	4100
17	51007	F17T8/850 T8 2'	1400	1330	24,000▲	85	25	Y	5000
25	51024	F25T8/735 T8 3'	2125	2020	24,000▲	75	25	Y	3500
25	51021	F25T8/741 T8 3'	2125	2020	24,000▲	75	25	Y	4100
25	51026	F25T8/835 T8 3'	2250	2110	24,000▲	85	25	Y	3500
25	51022	F25T8/841 T8 3'	2250	2110	24,000▲	85	25	Y	4100
25	51027	F25T8/850 T8 3'	2250	2110	24,000▲	85	25	Y	5000
32	51041	F32T8/730 T8 4'	2850	2720	24,000▲	75	25	Y	3000
32	51042	F32T8/735 T8 4'	2850	2720	24,000▲	75	25	Y	3500
32	51043	F32T8/741 T8 4'	2850	2720	24,000▲	75	25	Y	4100
32	51044	F32T8/750 T8 4'	2850	2720	24,000▲	75	25	Y	5000

MAX10494-10

All specifications are subject to change without notice



FCC Certified
ISO 9002 Certified
* UPC Codes

MaxLite™: 1-800-555-5629 Fax: 973-244-7300 info@maxlite.com www.maxlite.com

MaxLite West™: 1-800-793-1212 Fax: 909-944-1442 info@maxlite.com www.maxlite.com

PRODUCT FOCUS **XL SUPER T8 SERIES,
PREMIUM T8 & Watt Saver**
Linear Fluorescent Lamp

FB32T8/735 24,000 Hour (7) 6762751054 (0)*	FB32T8/741 24,000 Hour (7) 6762751055 (7)*	FB32T8/750 24,000 Hour (7) 6762751051 (9)*
FB32T8/835 24,000 Hour (7) 6762751052 (6)*	FB32T8/841 24,000 Hour (7) 6762751056 (4)*	FB32T8/850 24,000 Hour (7) 6762751057 (1)*



PREMIUM T8 SPECIFICATIONS

Watts	Order Code	Description	Lumens	Lamp Life (Hrs)	CRI	Case Pack	Cathode Guard	K
32	51054	FB32T8/735 T8 U-Bend'	2650	24,000▲	75	20	Y	3500
32	51055	FB32T8/741 T8 U-Bend'	2650	24,000▲	75	20	Y	4100
32	51051	FB32T8/750 T8 U-Bend'	2650	24,000▲	75	20	Y	5000
32	51052	FB32T8/835 T8 U-Bend'	2900	24,000▲	85	20	Y	3500
32	51056	FB32T8/841 T8 U-Bend'	2900	24,000▲	85	20	Y	4100
32	51057	FB32T8/850 T8 U-Bend'	2900	24,000▲	85	20	Y	5000

All specifications are subject to change without notice

SPECIAL NOTES	APPLICATIONS	LOCATIONS
<ul style="list-style-type: none"> >> System Warranty: System warranty is available on MaxLite Lamp and Ballast purchased together. Contact your local Sales Representative. >> ▲ 24,000 Hours on a 3 hr cycle; 30,000 Hours on a 12 hr cycle. 	<ul style="list-style-type: none"> • Industrial Lighting • Commercial Lighting • Residential Lighting 	<ul style="list-style-type: none"> • Office • Hotel/Motel • Schools/Hospital • Warehouse • Factory

BENEFITS	SPECIFICATIONS
<ul style="list-style-type: none"> • XL Super T8 & Premium Series: <ul style="list-style-type: none"> >> High lumen, Low mercury >> TCLP compliant <5mg> >> Finest blend of premium trichromatic rare earth phosphors • Watt Saver Series: <ul style="list-style-type: none"> >> For maximizing energy savings >> Low mercury - TCLP compliant 	<ul style="list-style-type: none"> • Ballast Type >> Electronic Ballast • Starting Method >> Instant Start • Input Line Voltage >> 120VAC • Input Line Frequency >> 50/60HZ • Minimum Starting Temp. >> 0°F • Max. Operating Temp. >> 100°F • Color Rendering Index >> 75/85

MAX10494-10

