





## LED LARGE ADJUSTABLE WALL PACK

### LAW74 SERIES



74W



## PRODUCT DESCRIPTION:

With flexible installation features and architectural-grade design, LED Large Adjustable Wall Packs offer discreet, but powerful lighting for outdoor locations. The wall packs are constructed with a fixture head that pivots up to 120 degrees, to precisely aim light while minimizing glare and backlight. Wall packs are issued unscrewed, so they are ready to install right out of the box.

## FEATURES:

- Fixture head pivots fully up to 120° from mounting plane
- Efficacy of 85 lm/W translates to as much as 70% energy savings over HID incumbents
- 70 CRI min
- Universal 120-277V power supply
- Power Factor > 0.9; THD < 25%
- 120,000-hour L70 lifetime, TM-21 standards @ 25°C

## CONTROLS:

**120VAC/208-277VAC Photocontrol:** Voltage-specific photocontrols power the fixture when light levels reach 20 lux or below, and turn it off at 30 lux or higher. Operating temperature of -30°F-120°F. Photocell mounted externally.

## CONSTRUCTION:

- Die-cast housing, durable powder coat finish
- Spirit level makes for an easy installation

### MODEL SELECTION (Full list of order codes on pg. 2)

Typical order example: LAW74U50PC27B

LAW74	U	LED50	B	
FAMILY	VOLTAGE	CCT	CONTROL	FINISH
LAW74= 74W, 250W Metal Halide equivalent	U= 120-277V	LED50= 5000K	(OMIT)= None, std PC12= 120V Photocontrol PC27= 277V Photocontrol	B= Bronze, std

### SPECIFICATIONS:

		LAW74U50B	LAW74U50BPC12	LAW74U50BPC27
ITEM	SPECIFICATION	DETAILS		
GENERAL PERFORMANCE	Lumens Delivered (lm)	6230		
	Efficacy (lm/W)	85		
	CCT	5000K		
	Lumen Maintenance (L70)	> 120,000 hours		
	Color Rendering Index (CRI)	70		
ELECTRICAL	Input Power (W)	74		
	Power Factor	> 0.9		
	Input Voltage (V)	100-277V, 50/60Hz	100-120V, 50/60Hz	208-277V, 50/60Hz
	Lens	Sealed borosilicate glass lens		
	Housing	Aluminum		
PHYSICAL	Mounting	Gasketed back plate can be mounted to recessed outlet box or direct to surface		
	Operating Temperature	-30°F-104°F		
APPLICATION	Certification	RoHS, cETLus, FCC, LM-79, LM-80, TM-21, DLC		
	Environment	IP66		
	Humidity	20% - 85% RH, non condensing		
	Warranty	5 Years		

### ORDERING\*:

ORDER CODE	MODEL	OPTIONS	EFFICACY (lm/w)	OUTPUT (LUMENS)	NOMINAL POWER (WATTS)	CCT	FINISH
74124	LAW74U50B	None	85	6230	74	5000K	Bronze
74125	LAW74U50PC12B	120V Photocontrol					
74126	LAW74U50PC27B	277V Photocontrol					

\*Please contact your MaxLite representative to order products that don't have order codes listed here.