

FLUORESCENT T5 VAPOR TIGHT LSVF SERIES



A cost-effective, specification-grade T5 Fluorescent Vapor Tight Fixture are constructed with full-length polycarbonate lenses and housings, and stainless steel closure hardware. The fixture meets applicable building safety codes and is ideal for use in utility lighting, parking garage and stairwell lighting.

PROJECT NAME	
CATALOG NUMBER	
NOTES	
FIXTURE TYPE	ROOM SCHEDULE

FEATURES:

- Programmed start electronic ballasts
- Stainless steel specification grade hasps and clips
- IP66 rated with hermetic sealing for wet environments
- Input wires are 7' for tandem wiring, eliminating back and end knockouts
- Ceiling or wall mounted
- White finish standard
- Field splicing
- Min Start Temp: -30° C



CONSTRUCTION:

- Polycarbonate housing with clear polycarbonate lens with inside ribbing
- Duplicate voltage 120/277v multivolt
- Programmed start electronic ballast

WARRANTY:

- One year warranty on material and workmanship
- Three year warranty on ballasts

ORDERING EXAMPLE: LSVF5006SD108X

Model Number	Order Number	Description	Dimensions (L"xW"xH")
LSVF5006SD108X	72101	VAPOR TIGHT LINEAR FLUORESCENT T5 2 LAMP x 54W 50IN 120/277V	50" x 6.2" x 4.0"

*All data subject to change

- Class P inherent thermal protection
- Surge protection (ANSI C62.41)
- EMI/RF: meets FCC 47CFR part 10 subpart C
- End of lamp protection circuit
- Type 1 outdoor
- IR non-interfering



FLUORESCENT T5 VAPOR TIGHT LSVF SERIES




SPECIFICATIONS:

ITEM	SPECIFICATION	DETAILS
GENERAL PERFORMANCE	Spacing Criteria	Available upon request
	Initial Lumens (using F54T5HO)	10,000
	Efficiency (using F54T5HO)	71%
	Number of Lamps (not Incl.)	2 x F54T5HO
ELECTRICAL	Ballast Type	Programmed start electronic
	Ballast Factor	1.0
	Maximum THD	<10%
	Input Voltage	120/277V multivolt
	Power Consumption (System Wattage)	115W
PHYSICAL	Dimensions (L x W x H)	50.0" x 6.2" x 4.0"
	Weight	8 lbs.
	Housing	Polycarbonate
	Lens	Ribbed polycarbonate clear
	Mounting	Ceiling surface mount or wall mounted
	Operating Temperature	-30°C to 55°C
CERTIFICATION	Certification	cETLus, FCC
	Material Usage	RoHS compliant, no mercury
	Environment	Indoor / outdoor– wet, IP66
	Warranty	5 year

Lighting layouts and spacing criteria available upon request

DIMENSIONS:



L= 50", W=6", H=3.75"

