



LED BULLET FLOOD


MLSB, MLLB SERIES



Side View



Front View



3/4 View

PRODUCT DESCRIPTION:

The outdoor rated LED bullet flood fixture is constructed with precision die cast aluminum housing and tempered glass with a 1/2" NPS threaded arm. It is ideal for use in landscape, façade and sign lighting applications. Fixture can be surface mounted directly to electrical boxes or posts with 1/2" threaded bushing.

FEATURES:

- 12W replaces up to 75 Watt Quartz
- 30W replaces up to 150 Watt Metal Halide
- Medium NEMA 5X5 field distribution
- Efficiency ranging from 70 to 86 lm/W
- 2700K, 3000K and 5000K available
- 50,000 hour L70 Life
- Universal 120-277V driver
- Maintenance free
- Fixture can be surface mounted directly to electrical boxes or posts with 1/2" threaded bushing
- 5 Year Limited Warranty
- IP65 rated
- CRI: ≥75
- 1/2" NPS threaded arm with locking swivel arm
- Bronze polyester powder coat finish

CONSTRUCTION:

- Die cast aluminum body
- Sealed to keep out dirt and bugs
- Tempered shatter resistant glass lens
- Weep hole located on lower lip of fixture to prevent water buildup

MODEL SELECTION (Full list of order codes on pg. 2)

Typical order example: MLLB30LED30

MODEL SELECTION (Full list of order codes on pg. 2)		Typical order example: MLLB30LED30	
FAMILY		CCT	
MLSB12= 12W, 50-75W Quartz Halogen equivalent MLLB30= 30W, 100-150W Metal Halide equivalent		LED30= 3000K LED50= 5000K	



LED Bullet Flood
MLSB, MLLB SERIES

SPECIFICATIONS:

		MLSB12LED30	MLSB12LED50	MLLB30LED30	MLLB30LED50
ITEM	SPECIFICATION	DETAILS			
GENERAL PERFORMANCE	Lumens Delivered (lm)	790	815	2115	2500
	Efficacy (lm/W)	77	74	70	86
	Beam Angle (H x V)	70° x 68°	68° x 69°	63° x 62°	65° x 60°
	CCT	3000K	5000K	3000K	5000K
	Lumen Maintenance (L70)	50,000 Hours			
	Color Rendering Index (CRI)	≥75			
ELECTRICAL	Input Power (W)	10	11	30	29
	Power Factor	> 0.9			
	Input Voltage (V)	120V-277V, 50/60Hz			
	Housing	Aluminum			
PHYSICAL	Mounting	½" NPS threaded arm with locking swivel arm			
	Operating Temperature	-30°F - 104°F			
APPLICATION	Environment	IP65			
	Humidity	20% - 85% RH, non condensing			
	Warranty	5 Years			

ORDERING*:

ORDER CODE	MODEL	EFFICACY (lm/W)	OUTPUT (LUMENS)	NOMINAL POWER (WATTS)	COLOR TEMPERATURE (CCT)
74113	MLSB12LED30	77	790	12	3000K
74209	MLLB30LED30	72	2115	30	
74114	MLSB12LED50	74	815	12	5000K
74210	MLLB30LED50	86	2500	30	

Lighting layouts and spacing criteria available upon request

*Please contact your MaxLite representative to order products that don't have order codes listed here.