

LED OMNIDIRECTIONAL A19 LAMP



MaxLite's ENERGY STAR®-qualified LED Omnidirectional A19 lamp is the most versatile light source in the market. It replicates a true A19 incandescent replacement lamp with a 300-degree beam angle that produces even light from the socket base and above in all directions. The seven-, 10- and 15-watt lamps replace a 40-, 60- and 75-watt incandescent bulb respectively. MaxLED®'s LED Omni A19 lamps can yield more than 80 percent savings in energy. Lumen maintenance is maximized by using a multi-layered and tapered heat sink.

PROJECT NAME
CATALOG NUMBER
NOTES
FIXTURE TYPE

FEATURES:

- 25,000 hour life (L70 standards)
- Proprietary housing for thermal heat protection
- CRI: 80
- Five year limited warranty
- Dimmable down to 10 percent
- Saves more than 80 percent on energy
- Power factor: > .9
- Standard E26 base

APPLICATIONS:

- Chandeliers
- Pendants
- Table and floor lamps
- Sconces
- Not for use in fully enclosed luminaires
- Suitable for use in damp locations



Lamp Ordering Information:

Watts	Order Number	Model Number	Incandescent Equivalent	Delivered Lumens	Efficacy	Beam	Lamp Life (Hrs.)	Dimensions	CCT
7	72182	SKBO07DLED27	40	450	64	300°	25,000	2.45" x 4.43"	2700
7	72077	SKBO07DLED30	40	450	65	300°	25,000	2.45" x 4.43"	3000
7	72183	SKBO07DLED41	40	475	68	300°	25,000	2.45" x 4.43"	4100
10	72185	SKBO10DLED27	60	760	76	300°	25,000	2.45" x 4.43"	2700
10	73505	SKBO10DLED30-E	60	800	80	300°	25,000	2.45" x 4.43"	3000
15	72228	SKBO15DLED27	75	1065	71	300°	25,000	2.75" x 5.10"	2700
15	72133	SKBO15DLED30	75	1100	73	300°	25,000	2.75" x 5.10"	3000
15	72227	SKBO15DLED41	75	1135	76	300°	25,000	2.75" x 5.10"	4100

MAX12210

Lighting layouts and spacing criteria are available upon request

*ENERGY STAR Qualified



OMNIDIRECTIONAL A19 LED LAMP



DIMENSIONS:



COMPATIBLE DIMMERS:

MAKE	DIMMER MODEL
Lutron	S-600H-WH
Lutron	MACL-153MH-WH
Lutron	D-600PH-DK
Lutron	CTCL-153PD
Leviton	L01-6683-1
Leviton	6631-1LW
Leviton	6633-P

