

# GU24 OMNIDIRECTIONAL A19 LED LAMP



MaxLite's LED GU24 Omni A19 lamps are the most versatile GU24-based light sources in the market. They replicate a true A19 incandescent replacement lamp with a 300-degree beam angle that produces even light from the socket base and above in all directions. The seven-, 10- and 15-watt GU24 lamps emit light equivalent to 40-, 60- and 75-watt incandescent bulbs respectively. MaxLED®'s LED Omni A19 Lamps can yield up to 85 percent savings in energy. Lumen maintenance is maximized by using a multi layer tapered heat sink.

## FEATURES:

- 2700K, 3000K & 4100K CCTs
- Proprietary housing for thermal heat protection
- CRI: 80
- Five year limited warranty
- Dimmable down to 10 percent
- Saves up to 85 percent on energy and operating costs
- Power factor: > .9
- Not for use in totally enclosed luminaires
- Suitable for use in dry or damp locations

## APPLICATIONS:

- Chandeliers
- Pendants
- Table and floor lamps
- Sconces
- Bathroom fixtures

## CONSTRUCTION:

**LEDs:** All LEDs are matched to ensure consistent color uniformity and CRI. The stated L70 life is based on functional light quality.

**Housing:** The body of each lamp is constructed of aluminum and plastic materials. The tiered heat sink promotes heat dissipation and features a tapered look. This keeps the LED junction temperature well below the manufacturer's specification. The temperature of the LED chips stay within proper thermal limits and the lumens are maintained for longer life.

**Base:** The Omni A19 lamp has a GU24 base.

### Lamp Ordering Information:

| Watts | Order Number | Model Number   | Incand. Equiv. Wattage | Delivered Lumens | Beam | Lamp Life (Hrs.) | Dimensions    | CCT  |
|-------|--------------|----------------|------------------------|------------------|------|------------------|---------------|------|
| 7     | 72343        | SKBO07GUDLED27 | 40                     | 435              | 300° | 25,000           | 2.45" X 4.43" | 2700 |
| 7     | 72078        | SKBO07GUDLED30 | 40                     | 450              | 300° | 25,000           | 2.45" X 4.43" | 3000 |
| 7     | 72550        | SKBO07GUDLED41 | 40                     | 460              | 300° | 25,000           | 2.45" X 4.43" | 4100 |
| 10    | 72342        | SKBO10GUDLED27 | 60                     | 770              | 300° | 25,000           | 2.45" X 4.43" | 2700 |
| 10    | 72063        | SKBO10GUDLED30 | 60                     | 800              | 300° | 25,000           | 2.45" X 4.43" | 3000 |
| 10    | 72215        | SKBO10GUDLED41 | 60                     | 825              | 300° | 25,000           | 2.45" X 4.43" | 4100 |
| 15    | 72229        | SKBO15GUDLED27 | 75                     | 1050             | 300° | 25,000           | 2.75" X 5.1"  | 2700 |
| 15    | 72134        | SKBO15GUDLED30 | 75                     | 1100             | 300° | 25,000           | 2.75" X 5.1"  | 3000 |
| 15    | 72230        | SKBO15GUDLED41 | 75                     | 1130             | 300° | 25,000           | 2.75" X 5.1"  | 4100 |

|                |
|----------------|
| PROJECT NAME   |
| CATALOG NUMBER |
| NOTES          |
| FIXTURE TYPE   |



Lighting layouts and spacing criteria available upon request

\*ENERGY STAR certified subcomponent

†Qualified on ENERGY STAR lamps program



# GU24 OMNIDIRECTIONAL A19 LED LAMP

## DIMENSIONS:



SKBO07GUDLED27  
SKBO07GUDLED30  
SKBO10GUDLED27  
SKBO10GUDLED30  
SKBO10GUDLED41



SKBO15GUDLED27  
SKBO15GUDLED30

## COMPATIBLE DIMMERS:

| MAKE    | DIMMER MODEL  |
|---------|---------------|
| Lutron  | TG-600PR      |
|         | S-600PR       |
|         | CT-103P       |
|         | CTCL-153      |
|         | DVCL-153L     |
|         | TGCL-153PH    |
| Leviton | cat.NO.6683-P |

