LED ECLIPSE

From the MaxLED® family of products, the LED Eclipse Lamp is a unique LED light sources that can be used in a wide variety of applications. With a high lumen output, flood beam angle distribution and superior heat management, Eclipse is an ideal lighting solution for residential, commercial, retail and hospitality applications. Its compact form makes it a great choice for recessed cans with open trims, bullet style track head fixtures and pendants.

FEATURES:

- Features patented Component Isolation Technology™
- Fully dimmable down to 10%
- Works with all standard incandescent dimming switches
- High power factor
- LM-80 qualified LEDs
- 50,000 hour life (L70 standards)
- Color matched LEDs
- Solid aluminum housing for thermal heat protection
- CRI: 82
- Fits most standard PAR38 and R40 diameter installations
- 5 year limited warranty

CONSTRUCTION:

Lamp Ordering Information:

LEDs: Constructed with industry leading LM-80 rated LEDs for long lasting performance. All LEDs are matched for color and CRI. 50,000 hour life is based on L70 standards, where after 30 percent depreciation, MaxLite considers the bulb to have reached its end of life, even though the lamp is still at 70 percent of initial lumens.

Housing: The body is solid aluminum, which acts as a heat-sink, providing thermal heat conductivity. This keeps the LED junction temperature within the required specifications. The lamp stays cool and the lumens are maintained for longer life. The molded fin shapes increase the surface area of the aluminum to provide more effective cooling.

PROJECT NAME CATALOG NUMBER NOTES FIXTURE TYPE



Base: Available in GU24 pin base and E26 Base

APPROVED DIMMERS

| Brand | Model |
|--------------------|------------|
| LUTRON | S-600 |
| LUTRON | LG-600P |
| LUTRON | CTCL-153PD |
| LUTRON | SELVB-300P |
| LEVITON | IPL06 |
| ARCTIC LIGHTING | PH3-A |
| SMART HOME | 2876D |
| LIGHTING | |

The manufacturer has certified this product to the California Energy Commission in accordance with California law.

| Watts | Order Code | Model Number | Lumens | Base | Life (Hrs.) L70 | Dimensions W" x H" | ССТ | | | |
|-------|---------------|-----------------|--------|------|--------------------|-----------------------|------|--|--|--|
| 17 | 71432 | SKE17DLED30 | 1010 | E26 | 50,000 | 5 x 3.27 | 3000 | | | |
| 17 | 71431 | SKE17DLED41 | 1140 | E26 | 50,000 | 5 x 3.27 | 4100 | | | |
| 17 | 71430 | SKE17DLED50 | 1100 | E26 | 50,000 | 5 x 3.27 | 5000 | | | |
| 17 | 71426 | SKE17GUDLED30 | 1010 | GU24 | 50,000 | 5 x 2.63 | 3000 | | | |
| 17 | 71427 | SKE17GUDLED41 | 1140 | GU24 | 50,000 | 5 x 2.63 | 4100 | | | |

Lighting layouts and spacing criteria available upon request





