



Energy Efficient Lighting Products

Model No.	SKEU322HEH/SC
Ballast Type	Electronic
Lamp Operation	Parallel / Instant start
Input Voltage	120-277
Frequency	50/60hz

SPECIFICATION

Lamp Type	No. of Lamps	Input Voltage (V)	Input Current (A)	Input Power (W)	Power Factor	MAX THD (%)	Ballast Factor	Min. Starting Temperature (°F)	Lamp Current Crest Factor	B.E.F.
F32T8 32W	2	120/277	0.64/0.27	76/75	>0.98	<10%	1.19	0°F	1.7	1.57/1.59
F17T8 17W	1	120/277	0.21/0.10	23	>0.98	<10%	1.41	0°F	1.7	6.13
F17T8 17W	2	120/277	0.34/0.15	38	>0.98	<10%	1.23	0°F	1.7	3.24
F25T8 25W	1	120/277	0.29/0.13	35	>0.98	<15 %	1.4	0°F	1.7	4.00
F25T8 25W	2	120/277	0.45/0.20	54	>0.98	<10%	1.2	0°F	1.7	2.22
F32T8/ES 25W	1	120/277	0.31/0.14	37	>0.98	<10%	1.4	0°F	1.7	3.78
F32T8/ES 25W	2	120/277	0.51/0.22	60	>0.98	<10%	1.19	0°F	1.7	1.98
F32T8/ES 28W	1	120/277	0.34/0.16	40	>0.98	<10%	1.4	0°F	1.7	3.50
F32T8/ES 28W	2	120/277	0.57/0.25	67	>0.98	<10%	1.19	0°F	1.7	1.78
F32T8/ES 30W	1	120/277	0.35/0.16	42	>0.98	<10%	1.38	0°F	1.7	3.29
F32T8/ES 30W	2	120/277	0.61/0.27	72	>0.98	<10%	1.19	0°F	1.7	1.65
F32T8 32W	1	120/277	0.37/0.17	45	>0.98	<10%	1.37	0°F	1.7	3.04
F40T8 40W	1	120/277	0.45/0.20	54/53	>0.98	<10%	1.35	0°F	1.7	2.5/2.55

Performance:

- Meets ANSI Standard C82.11
- Meets ANSI Standard C62.41
- Meets FCC Part 18 Class A (non-Consumer Limits)
- CEE "Higher Lumen" 32W T8 Lighting System

Safety:

- No PCBs
- UL/CUL Listed
- Class P, Type 1 Outdoor
- OCV 600v

Application:

- Remote Mounting: 18 ft. Max. overall lead length, 18AWG
- Maximum Case Temperature 75°C / 167° F
- Sound Rated - "A"
- Maximum Ambient Temperature 40°C / 105° F

Case	Inches
Length (L)	9.5
Width (W)	1.3
Height (H)	1
Mounting (M)	8.91
Weight	1.10 lbs.

Lead Length	Inches (+/-1)
Black	25
White	25
Red	46
Blue	31
Yellow	N/A

