



Energy Efficient Lighting Products

Model No.	SKEU322HEL/SC
Ballast Type	Electronic
Lamp Operation	Parallel / Instant start
Input Voltage	120-277
Frequency	50/60hz

SPECIFICATION

Lamp Type	No. of Lamps	Input Voltage (V)	Input Current (A)	Input Power (W)	Power Factor	MAX THD (%)	Ballast Factor	Min. Starting Temperature (°F)	Lamp Current Crest Factor	B.E.F.
F32T8 32W	2	120/277	0.40/0.17	48/47	>0.98	<10%	0.77	0°F	1.7	1.60/1.62
F17T8 17W	1	120/277	0.15/0.07	18	>0.98	<10%	0.9	0°F	1.7	5.00
F17T8 17W	2	120/277	0.23/0.10	27	>0.98	<10%	0.85	0°F	1.7	3.15
F25T8 25W	1	120/277	0.20/0.09	24	>0.98	<10%	0.9	0°F	1.7	3.75
F25T8 25W	2	120/277	0.32/0.14	39	>0.98	<10%	0.78	0°F	1.7	2.00
F32T8/ES 25W	1	120/277	0.20/0.09	24	>0.98	<10%	0.9	0°F	1.7	3.75
F32T8/ES 25W	2	120/277	0.33/0.14	39	>0.98	<10%	0.77	0°F	1.7	1.97
F32T8/ES 28W	1	120/277	0.22/0.10	26	>0.98	<10%	0.9	0°F	1.7	3.46
F32T8/ES 28W	2	120/277	0.37/0.16	43	>0.98	<10%	0.77	0°F	1.7	1.79
F32T8/ES 30W	1	120/277	0.24/0.11	28	>0.98	<10%	0.9	0°F	1.7	3.21
F32T8/ES 30W	2	120/277	0.39/0.17	46	>0.98	<10%	0.77	0°F	1.7	1.67
F32T8 32W	1	120/277	0.26/0.11	31	>0.98	<10%	0.9	0°F	1.7	2.90
F40T8 40W	1	120/277	0.29/0.13	36	>0.98	<10%	0.88	0°F	1.7	2.44

Performance:

- Meets ANSI Standard C82.11
- Meets ANSI Standard C62.41
- Meets FCC Part 18 Class A (non-Consumer Limits)
- CEE "High Performance" & "Reduced Wattage" 32W T8 Lighting System

Safety:

- No PCBs
- UL/CUL Listed
- Class P, Type 1 Outdoor
- OCV 600v

Application:

- Remote Mounting: 18 ft. Max. overall lead length, 18AWG
- Maximum Case Temperature 75°C / 167° F
- Sound Rated - "A"
- Maximum Ambient Temperature 40°C / 105° F

Case	Inches
Length (L)	9.5
Width (W)	1.3
Height (H)	1
Mounting (M)	8.91
Weight (lbs.)	1.1

Lead Length	Inches (+/-1)
Black	25
White	25
Red	46
Blue	31
Yellow	N/A

