



Model No.	SKEU323H/SC
Ballast Type	Electronic
Lamp Operation	Parallel / Instant start
Input Voltage	120-277
Frequency	50/60hz

SPECIFICATION

Lamp Type	No. of Lamps	Input Voltage (V)	Input Current (A)	Input Power (W)	Power Factor	MAX THD (%)	Ballast Factor	Min. Starting Temperature (°F)	Lamp Current Crest Factor	B.E.F.
F32T8 32W	3	120/277	0.91/0.39	109/107	>0.98	<10%	1.18	0°F	1.7	1.08/1.10
F25T8 25W	3	120/277	0.69/0.30	83/81	>0.98	<10%	1.16	0°F	1.7	1.40/1.43
F17T8 17W	3	120/277	0.49/0.22	60/58	>0.98/>0.98	<10%	1.19	0°F	1.7	1.98/2.05
F40T8 40W	2	120/277	0.84/0.36	101/100	>0.98	<10%	1.26	32°F	1.7	1.25/1.26
F32T8 32W	2	120/277	0.69/0.30	83/81	>0.98	<10%	1.27	0°F	1.7	1.53/1.57
F25T8 25W	2	120/277	0.55/0.25	66	>0.98	<10%	1.28	0°F	1.7	1.94

Performance:

- Meets ANSI Standard C82.11
- Meets ANSI Standard C62.41
- Meets FCC Part 18 Class B (Consumer Limits)
- CEE "High Performance" 32W T8 Lighting System

Safety:

- No PCBs
- UL/CUL Listed
- Class P, Type 1 Outdoor
- OCV 600v

Application:

- Remote Mounting: 18 ft. Max. overall lead length, 18AWG
- Maximum Case Temperature 75°C / 167° F
- Sound Rated - "A"
- Maximum Ambient Temperature 40°C / 105° F

Case	Inches
Length (L)	9.5
Width (W)	1.3
Height (H)	1
Mounting (M)	8.91
Weight (lbs.)	1.1

Lead Length	Inches (+/-1)
Black	25
White	25
Red	46
Blue	31
Yellow	N/A

